

Article

SCM420B9W
SCM420B9W INLET 20A 3P 4W IP67 9h

Picture




Master data

Minimum order	1 NR
Net Weight	0.212 KG
EAN code	8001636264844
INTRASTAT code	85366990

TechData

Synthetical description	APPLIANCE INLET
Protection degree	IP67
Commercial series	EUREKA[PIN&SLEEVE] Series
Flange	120X120MM
Rated current	20A
Poles	3P 4W
Rated voltage	3Ø250V
Colour	BLUE
Hour position	9h

Approvals and Certifications

 C UL US LISTED (USA)
Underwriters Laboratories Inc.








Standards and Laws

-  UL 1682
[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
-  UL 486E
[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors
-  CSA C22.2 No. 182.1 (1988)
[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
-  CSA C22.2 No. 65-93
[Canadian Standard] Wire connectors wiring products

Packaging

Description	Carton
Quantity	5
EAN code	8001636710983
Gross weight	1.675 KG
Volume	14822.625 CCM
Dimensions	235x435x145 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.335 KG
Volume	1718.75 CCM
Dimensions	125x125x110 (MM)

Annexed

-  Instruction manual
-  Technical drawing [DWG]

-  Technical drawing [PDF]

-  Technical drawing [STP]


Note:

> UL listed

