

Article**SCM420C7W**

SCM420C7W CONNECTOR 20A 3P 4W IP67 7h

Picture**Master data**

Minimum order	1 NR
Net Weight	0.247 KG
EAN code	8001636226422
INTRASTAT code	85366990

TechData

Synthetical description	CONNECTOR
Protection degree	IP67
Commercial series	EUREKA[PIN&SLEEVE] Series
Cable outlet	CABLE GLAND
Rated current	20A
Poles	3P 4W
Rated voltage	3Ø480V
Colour	RED
Hour position	7h

Approvals and Certifications

UL CLASSIFIED (USA)
Underwriters Laboratories Inc.

Standards and Laws

UL 1682
[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service



IEC 60309-1 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



IEC 60309-2 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories



UL 486E
[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors



CSA C22.2 No. 182.1 (1988)
[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products



CSA C22.2 No. 65-93
[Canadian Standard] Wire connectors wiring products

Packaging

Description	Carton
Quantity	5
EAN code	8001636677323
Gross weight	2.065 KG
Volume	21238 CCM
Dimensions	370x410x140 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.413 KG
Volume	2150 CCM
Dimensions	100x215x100 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

UL listed

