

Article

SCM420R7W
SCM420R7W RECEPTACLE 20A 3P 4W IP67 7h

Picture



Master data

Minimum order	1 NR
Net Weight	0.2 KG
EAN code	8001636204208
INTRASTAT code	85366990

TechData

Synthetical description	RECEPTACLE
Protection degree	IP67
Commercial series	EUREKA[PIN&SLEEVE] Series
Flange	75X75MM
Rated current	20A
Poles	3P 4W
Rated voltage	3Ø480V
Colour	RED
Hour position	7h

Approvals and Certifications



UL CLASSIFIED (USA)
Underwriters Laboratories Inc.



C UL US LISTED (USA)
Underwriters Laboratories Inc.

Standards and Laws



UL 1682
[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service



IEC 60309-1 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



IEC 60309-2 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories



UL 486E
[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors



CSA C22.2 No. 182.1 (1988)
[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products



CSA C22.2 No. 65-93
[Canadian Standard] Wire connectors wiring products

Packaging

Description	Carton
Quantity	5
EAN code	8001636659084
Gross weight	1.475 KG
Volume	11238.75 CCM
Dimensions	150x555x135 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.295 KG
Volume	1250 CCM
Dimensions	100x100x125 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

UL listed

