

Article

SCM5100C9W
SCM5100C9W CONNECTOR 100A 4P 5W IP67 9h

Picture






Master data

Minimum order	1 NR
Net Weight	1.761 KG
EAN code	8001636218328
INTRASTAT code	85366990




TechData

Synthetical description	CONNECTOR
Protection degree	IP67
Commercial series	EUREKA[PIN&SLEEVE] Series
Cable outlet	CABLE GLAND
Rated current	100A
Poles	4P 5W
Rated voltage	3ØY120/208V
Colour	BLUE
Hour position	9h

Approvals and Certifications

-  UE
Declaration of conformity
-  UL CLASSIFIED (USA)
Underwriters Laboratories Inc.
-  C UL US LISTED (USA)
Underwriters Laboratories Inc.

Standards and Laws

-  UL 1682
[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
-  IEC 60309-1 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
-  IEC 60309-2 (1999)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories



UL 486E
[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors



CSA C22.2 No. 182.1 (1988)
[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products



CSA C22.2 No. 65-93
[Canadian Standard] Wire connectors wiring products

Packaging

Description	Box
Quantity	1
EAN code	
Gross weight	1.994 KG
Volume	6287.625 CCM
Dimensions	135x345x135 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

> UL listed

> Dual ratings - Products with dual classification: Series I (International) and Series II (North America)