

**Article**

**SCM320B7W**  
SCM320B7W INLET 20A 2P 3W IP67 7h

**Picture**




**Master data**

Minimum order	1 NR
Net Weight	0.189 KG
EAN code	8001636218809
INTRASTAT code	85366990

**TechData**

Synthetical description	APPLIANCE INLET
Protection degree	IP67
Commercial series	EUREKA[PIN&SLEEVE] Series
Flange	120X120MM
Rated current	20A
Poles	2P 3W
Rated voltage	480V
Colour	RED
Hour position	7h

**Approvals and Certifications**

 C UL US LISTED (USA)  
Underwriters Laboratories Inc.








**Standards and Laws**

-  UL 1682  
[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
-  UL 486E  
[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors
-  CSA C22.2 No. 182.1 (1988)  
[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products
-  CSA C22.2 No. 65-93  
[Canadian Standard] Wire connectors wiring products

**Packaging**

Description	Carton
Quantity	5
EAN code	8001636668048
Gross weight	1.56 KG
Volume	14822.625 CCM
Dimensions	235x435x145 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.312 KG
Volume	1718.75 CCM
Dimensions	125x125x110 (MM)

**Annexed**

-  Instruction manual
-  Technical drawing [DWG]  

-  Technical drawing [PDF]  

-  Technical drawing [STP]  


**Note:**

> UL listed

