

Article

SCM430MI9W
SCM430MI9W MEC. INT. 30A 3P 4W 9h

Picture





Master data

Minimum order	1 NR
Net Weight	2.649 KG
EAN code	8001636318356
INTRASTAT code	85366990

TechData

Synthetical description	INTERLOCKED SOCKET
Protection degree	IP66/IP67/IP69
Commercial series	ADVANCE-GRP[PIN&SLEEVE] Series
Rated current	30A
Poles	3P 4W
Rated voltage	3Ø250V
Colour	BLUE
Hour position	9h

Approvals and Certifications

-  UE
Declaration of conformity
-  C UL US LISTED (USA)
Underwriters Laboratories Inc.

Standards and Laws

-  UL 508
[American Standard] Industrial Control Equipment
-  IEC 60309-1 (2012)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes.
- Part 1: General requirements
-  IEC 60309-2 (2012)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes.
- Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories
-  IEC 60309-4 (2012)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes.
Part 4: Switched socket-outlets and connectors with or without interlock



UL 60947-1
[American Standard] Low-Voltage
Switchgear and Controlgear - Part 1:
General rules



UL 60947-4-1
[American Standard] Low-Voltage
Switchgear and Controlgear - Part 4-1:
Contactors and Motor-Starters -
Electromechanical Contactors and Motor-
Starters



CSA C22.2 No. 60947-1-13
[Canadian Standard] Low-voltage
switchgear and controlgear - Part 1: General
rules



CSA C22.2 No. 60947-4-1-14
[Canadian Standard] Low-voltage
switchgear and controlgear - Part 4-1:
Contactors and motor-starters -
Electromechanical contactors and motor-
starters

Packaging

Description	Carton
Quantity	6
EAN code	8001636755656
Gross weight	17.724 KG
Volume	54816.125 CCM
Dimensions	305x455x395 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	2.954 KG
Volume	7227.5 CCM
Dimensions	140x295x175 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- >
UL listed
✘
- ✘
With power indicating led
✘
- >
Already supplied with simple single
bottom
✘