

Article

SCM460MI7W
SCM460MI7W MEC. INT. 60A 3P 4W 7h

Picture



Master data

Minimum order	1 NR
Net Weight	5.507 KG
EAN code	8001636304670
INTRASTAT code	85366990

TechData

Synthetical description	INTERLOCKED SOCKET
Protection degree	IP66/IP67/IP69
Commercial series	ADVANCE-GRP[PIN&SLEEVE] Series
Rated current	60A
Poles	3P 4W
Rated voltage	3Ø480V
Colour	RED
Hour position	7h

Approvals and Certifications



UE
Declaration of conformity



C UL US LISTED (USA)
Underwriters Laboratories Inc.

Standards and Laws



UL 508
[American Standard] Industrial Control Equipment



IEC 60309-1 (2012)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes.
- Part 1: General requirements



IEC 60309-2 (2012)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes.
- Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories



IEC 60309-4 (2012)
[International Standard] Plugs, socket-outlets and couplers for industrial purposes.
Part 4: Switched socket-outlets and connectors with or without interlock



UL 60947-1
[American Standard] Low-Voltage
Switchgear and Controlgear - Part 1:
General rules



UL 60947-4-1
[American Standard] Low-Voltage
Switchgear and Controlgear - Part 4-1:
Contactors and Motor-Starters -
Electromechanical Contactors and Motor-
Starters



CSA C22.2 No. 60947-1-13
[Canadian Standard] Low-voltage
switchgear and controlgear - Part 1: General
rules



CSA C22.2 No. 60947-4-1-14
[Canadian Standard] Low-voltage
switchgear and controlgear - Part 4-1:
Contactors and motor-starters -
Electromechanical contactors and motor-
starters

Packaging

Description	Carton
Quantity	1
EAN code	
Gross weight	5.908 KG
Volume	17226 CCM
Dimensions	180x435x220 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

> UL listed

With power indicating led

> Already supplied with simple single bottom