

**Article**

**SCM460P9W**

SCM460P9W PLUG 60A 3P 4W IP67 9h

**Picture**






**Master data**

Minimum order	1 NR
Net Weight	0.732 KG
EAN code	8001636150031
INTRASTAT code	85366990




**TechData**

Synthetical description	PLUG
Protection degree	IP67
Commercial series	EUREKA[PIN&SLEEVE] Series
Cable outlet	CABLE GLAND
Rated current	60A
Poles	3P 4W
Rated voltage	3Ø250V
Colour	BLUE
Hour position	9h

**Approvals and Certifications**

-  UE  
Declaration of conformity
-  UL CLASSIFIED (USA)  
Underwriters Laboratories Inc.
-  C UL US LISTED (USA)  
Underwriters Laboratories Inc.

**Standards and Laws**

-  UL 1682  
[American Standard] Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type and MIL-C-5756C: 600-volt heavy duty, portable, power, single and multiconductor, electrical cable for severe flexing service
-  IEC 60309-1 (1999)  
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
-  IEC 60309-2 (1999)  
[International Standard] Plugs, socket-outlets and couplers for industrial purposes. Part: 2: Dimensional interchangeability requirements for pin and contact-tube accessories



UL 486E  
[American Standard] Equipment wiring terminals for use with aluminium and/or copper conductors



CSA C22.2 No. 182.1 (1988)  
[Canadian Standard] Industrial Locking Type, Special Use Attachment Plugs, Receptacles, and Connectors, Wiring Products



CSA C22.2 No. 65-93  
[Canadian Standard] Wire connectors wiring products

### Packaging

Description	Box
Quantity	1
EAN code	8001636581125
Gross weight	0.926 KG
Volume	4032 CCM
Dimensions	120x280x120 (MM)

### Annexed



Instruction manual



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp

### Note:

> UL listed



> Dual ratings - Products with dual classification: Series I (International) and Series II (North America)

